



NON MANDREL

MD070



FEATURES

- Standard steel tube capacity 38 x 1.5 mm
- Pipe capacity 1" Sch. 10
- Square tube capacity 25 x 25 x 3 mm
- Bending radii 36 ÷ 190 mm
- Bend to CLR as small as 2D
- Patented quick-change tooling system with multiple radii available
- Remote foot pedal for hands free operation
- Patented swing away counterbending die vise
- No hydraulic components
- Control digital setting
- Ships with carrying case and tool kit

TECHNICAL DATA

| | |
|----------------------------------|---------------------|
| Flection Modulus | 2.3 cm ³ |
| Minimum Outside Diameter | 10 mm - 1/8" Gas |
| Maximum Shaft Speed | 2.8 rpm |
| Maximum Center Line Radius (CLR) | 190 mm |
| Minimum Center Line Radius (CLR) | 36 mm |
| Power | 900 W |
| Voltage Requirement | 110 - 220 V |
| Weight | 23 Kg |
| Dimensions (L x W x H) | 245 x 300 x 320 mm |

| | MAXIMUM CAPACITY | MD070 |
|--|--|----------------|
| | Gas tubes | 1" Gas x 3.4 |
| | Standard Steel tubes | 38 x 1.5 mm |
| | Furniture tubes | 38 x 1.5 mm |
| | Hydraulic Steel ST35 | 35 x 3 mm |
| | Stainless Steel AISI 304 - 316 | 35 x 2 mm |
| | Stainless Steel AISI 308 (food industry) | 35 x 1.5 mm |
| | Soft Brass | 42 x 1.5 mm |
| | Hard Copper & Aluminium | 42 x 1.5 mm |
| | Soft Copper | 50 x 2 mm |
| | Conduit tubes | 50 x 2 mm |
| | Mepla, Geberit and similar tubes | 50 x 4 mm |
| | Mild Steel (EN: S275JO) | 20 mm |
| | Mild Steel (EN: S275JO) | 10 x 25 mm |
| | Mild Steel (EN: S275JO) | 15 x 25 x 3 mm |
| | Mild Steel (EN: S275JO) | 25 x 25 x 3 mm |
| | Mild Steel (EN: S275JO) | 20 x 20 mm |
| | Mild Steel (EN: S275JO) | 30 x 30 x 5 mm |
| | Mild Steel (EN: S275JO) | 30 x 15 x 5 mm |

MAXIMUM CAPACITIES AND MINIMUM RADII ARE INDICATIVE AND NOT BINDING