



### P36

BUILT WITH A HEAVY CARRYING STRUCTURE. THE AXIAL GEARS IN FORGED AND PROCESSED STEEL AND ALL ROTARY ORGANS ARE ENCLOSED IN AN OIL BATH IN THE REDUCTION GEARBOX IN A STRONG ROLLED SECTION. AN AMBIVALENT WORKING BENCH ALLOWS ANY TYPE OF BENDING WITHOUT SHIFTING THE BAR; BESIDES, IT IS POSSIBLE TO MODIFY THE TYPE OF BEND THROUGH SHIFTING THE PEG IN THE HOLES ON THE WORKING BENCH. THE CONTROLS ALLOWS STOPPING AND RECYCLING AT ANY TIME DURING THE PROCESS. LOW VOLTAGE ELECTRICAL CONTROL EQUIPMENT (24 VOLT).

P36 IS WELL PROVIDED :

- DOUBLE BENDING WITH ROTATING PLATE 350mm.
- BUSHES FROM 60mm. TO 120mm.
- MOTOR HP4
- 1 CHECKING BLOCK
- 1 STIRRUP BENDING PIN
- 1 SQUARE PIN
- 3 BUSH HOLDING PINS+1 PEDAL+1 SET OF BUSHES
- BRACKET BENDER GAUGE, SPIRAL COLLER AND DUAL BENDER ARE AVAILABLE ON RE

P36			
DIMENSIONS	86 X 85 X 85		
WEIGHT	Kg 400		
OIL CAPACITY	Lt. 12		
BENDING CAPACITY			
	1 bar	2 bars	3 bars
R 45 KG/mm2	36 mm	26 mm	22 mm
R 65 KG/mm2	32 mm	24 mm	18 mm
R 80 KG/mm2	30 mm	22 mm	16 mm

**EXTRA PANEL CONTROL TO STORAGE UP TO 5 BENDS ON SEQUENCE**

