



FEATURES

- Standard steel tube capacity 35 x 2.5 mm
- Pipe capacity 1" Sch. 10
- Square tube capacity 25 x 25 x 3 mm
- Bending radii 10 ÷ 190 mm
- Bend to CLR as small as 2D
- Very simple machine and light machine
- No hydraulic or electric components
- Ships with carrying case and tool kit

TECHNICAL DATA

Flection Modulus	2.3 cm ³
Minimum Outside Diameter	10 mm - 1/8" Gas
Maximum Shaft Speed	-
Maximum Center Line Radius (CLR)	190 mm
Minimum Center Line Radius (CLR)	10 mm
Power	-
Voltage Requirement	-
Weight	17 Kg
Dimensions (L x W x H)	245 x 200 x 320 mm

	MAXIMUM CAPACITY	MD083
	Gas tubes	1" Gas x 3.4
	Standard Steel tubes	35 x 2.5 mm
	Furniture tubes	32 x 1.5 mm
	Hydraulic Steel ST35	35 x 3 mm
	Stainless Steel AISI 304 - 316	35 x 2 mm
	Stainless Steel AISI 308 (food industry)	35 x 1.5 mm
	Soft Brass	32 x 3 mm
	Hard Copper & Aluminium	42 x 1.5 mm
	Soft Copper	50 x 2 mm
	Conduit tubes	50 x 2 mm
	Mepla, Geberit and similar tubes	50 x 4 mm
	Mild Steel (EN: S275JO)	20 mm
	Mild Steel (EN: S275JO)	10 x 25 mm
	Mild Steel (EN: S275JO)	15 x 25 x 3 mm
	Mild Steel (EN: S275JO)	25 x 25 x 3 mm
	Mild Steel (EN: S275JO)	20 x 20 mm
	Mild Steel (EN: S275JO)	30 x 30 x 5 mm
	Mild Steel (EN: S275JO)	30 x 15 x 5 mm

MAXIMUM CAPACITIES AND MINIMUM RADI ARE INDICATIVE AND NOT BINDING

NON MANDREL BENDERS